

# MALE PCB PINS

## PRINTED CIRCUIT PINS

<p><b>1958</b> 1958-0-00-15-00-00-03-0 Target contact, Solder Tail Concave face for increased surface contact</p>	<p><b>1960</b> 1960-0-00-15-00-00-03-0 Target contact, Solder Tail Concave face for increased surface contact</p>	<p><b>1831</b> 1831-1-00-15-00-00-03-0 Target contact, Solder Tail Concave face for increased surface contact</p>	<p><b>1931</b> 1931-1-00-15-00-00-03-0 Hex press-fit in .034 mounting hole</p>
<p><b>1953</b> 1953-0-00-XX-00-00-03-0 Press-fit in .054 mounting hole</p>	<p><b>1954</b> 1954-0-00-XX-00-00-03-0 Press-fit in .054 mounting hole</p>	<p><b>1955</b> 1955-0-00-15-00-00-03-0 Target contact, surface mount Concave face for increased surface contact</p>	<p><b>1957</b> 1957-0-00-15-00-00-03-0 Target contact, surface mount Concave face for increased surface contact</p>
<p><b>1933</b> 1933-0-00-XX-00-00-03-0 Press-fit in .034 mounting hole</p>	<p><b>1935</b> 1935-0-00-XX-00-00-03-0 Press-fit in .034 mounting hole</p>	<p><b>1934</b> 1934-0-00-15-00-00-03-0 Target contact, Solder Tail Concave face for increased surface contact</p>	<p><b>1936</b> 1936-0-00-15-00-00-03-0 Target contact, surface mount Concave face for increased surface contact</p>

### SPECIFICATIONS:

**Pin Material:** Brass Alloy 360, 1/2 Hard  
(Except where noted)

**Dimensions:** Inches

**Tolerances On:** Lengths:  $\pm .005$   
Diameters:  $\pm .002$   
Angles:  $\pm 2^\circ$



ORDER CODE: XXXX - 0 - 00 - XX - 00 - 00 - 03 - 0

BASIC PART #

SPECIFY PIN FINISH:

- 01 200  $\mu$ " TIN/LEAD OVER NICKEL
- ◆ 80 200  $\mu$ " TIN OVER NICKEL (RoHS)
- ◆ 15 10  $\mu$ " GOLD OVER NICKEL (RoHS)
- ◆ 21 20  $\mu$ " GOLD OVER NICKEL (RoHS)
- ◆ 34 50  $\mu$ " GOLD OVER NICKEL (RoHS)

