



NOTES:

1. METALSHELLS: STEEL; min. 315µin TIN over 40-80µin NICKEL
2. INSULATORS: PBT GF UL 94 V-0; GREEN
3. SIGNAL CONTACTS: COPPER ALLOY
PLATING: GOLD FLASH over NICKEL
SOLDER CUP ACCEPTS CABLE AWG 20
4. NO CONTACT ON POS. A1
5. CONNECTOR IS PART MARKED: 3047W1PAM99A10X CONEC ABC

Directive 2002/95/EC RoHS compliant

| | | | | | | |
|---|-------------|----------|--------------|--------------------------|---|--|
| THIS DRAWING MAY NOT BE COPIED OR REPRODUCED IN ANY WAY, AND MAY NOT BE PASSED ON TO A THIRD PARTY WITHOUT WRITTEN PERMISSION. OWNERSHIP AND COPYRIGHT OF CONEC GmbH DO NOT ALTER CAD DRAWING BY HAND | tolerance | | dim. in mm | | scale: 2:1 (5:1) | |
| | | | | | material: SEE NOTES | |
| | drawn | 01.08.11 | Lehmenkühler | | title: D-SUB COMBINATION MALE 47W1P SOLDER CUP | |
| | appd. | 01.08.11 | Fischer | | | |
| | norm | | | | | |
| d-old | | | | dwg no: Inventor 10 | DIN-A3 | |
| a | Original | | | 13K2A2247 | | |
| rev. | description | date | name | part no: 3047W1PAM99A10X | | |



sh: 1