

APPLICATOR PARTS LIST

TYPE

LENGTHWISE

RING
AMPLINAR
STUD RETAINING

AMP INCORPORATED
HARRISBURG, PENNA.

THIS DRAWING IS A CONTROLLED DOCUMENT.

NO.	DESCRIPTION	REQ.	PART NO.	NO.	DESCRIPTION	REQ.	PART NO.	
1	WIRE CRIMPER	1	456408-6	42	BENDING TOOL	1	458961-4	
2	INS. CRIMPER			43				
3	ANVIL	1	2-473405-5	44				
4	ANVIL SPACER			45				
5	SHEAR BLADE	1	375307	46				
6	REAR SHEAR PLATE	1	385013-4	47				
7	SHEAR BLADE SPACER	2	370748	48				
8	FRONT BEND. PLATE	1	F-386017-5	49				
9	REAR ANVIL SPACER PLT.			50				
10	FRONT ANVIL SPACER PLT.	1	F-387158-6	51				
11	TOOL SPACER	1	470493-6	52				
12	SPACER	1	F-470493-4	53				
13	FRONT STRIP GUIDE	1	B10144-1	54				
14	REAR STRIP GUIDE	1	B10144-2	55				
15	RAM	1	471167	56				
16	TOOL HOLDER	1	376046	57	SCREW, DRIVE	3	21017-6	
17	ADJ. CRIMP MOUNT			58	PLATE, IDENTIFICATION	1	452373-1	
18	ADJ. BLOCK			59				
19	APPLICATOR MOUNT ASSY.	1	570656	60				
20	BASE PLATE			61				
21	BASE BLOCK			62				
22	STRIP GUIDE PLATE			63				
23	ANVIL HOLDER	1	370526	64				
24	AUX. ANVIL HOLDER	1	377515	65	TENSION ADJ PLATE	1	374997	
25	STRIPPER	1	811654-2	66	MISCELLANEOUS			
26	STRIPPER MOUNT	2	386231	67	AIR FEED ASSY			
27	RETAINER PLATE	2	372251	68	TOOL HOLDER			
28	STRIPPER MOUNT BRACKET			69	AIR FEED DELAY ASSY	1	809806-1	
29	STRIPPER BUSHING			70	LUBRICATOR ASSY	1	46518A-2	
30	STOCK DRAG	1	375381	71	TERMINAL LUBRICANT	1	22014-1	
31	STOCK DRAG HANDLE			72	AIR FEED ASSY 2"	1	690021	
32	STOCK DRAG STUD	2	354045-1	REV.	REVISION RECORD	DATE	BY	ECN
33	STOCK DRAG SPRING	2	1-23347-1	A	ECN R-6296	6-85	HA/EE	
34	STOCK DRAG ADJ. SCREW	2	372997	B	ECN R-6488	10-85	HA/EE	
35	FEED FINGER HOLDER			C	EC-A-262690	8-6-90	HA/EE	
36	FEED FINGER	1	375093	D	0150-6407-95	9/95	LSC/EE	
37	FEED FINGER TIP			E	0150-6525-95	11/95	LSC/EE	
38	FEED FINGER SPACER			F	ECN 0150-9329-99	5-99	JTB	
39	BASE CASTING	1	570238	G	0150-9462-99	7-99	JTB	
40	GUARD	1	457664-7					
41								

CRIMPING DATA			TERMINALS
TO APPLY TERMINAL			505017
MAG			
WIRE SIZE	CRIMP HEIGHT		
20	.054		
18	.057		
16	.062		WITH LEG
			505072
CRIMP	SIZE	TYPE	FEED
WIRE	.110	F	
INSUL.			1.000
SLEEVED			
INSULATION RANGE	WIRE RANGE		
	20-16 MAG		

EXPLODED VIEW
A-6000 A-6000-1

REMARKS:
TOP TOOL MTG:
ITEM 5, 12, 42, 11, 1

BOTTOM TOOL MTG:
ITEM 6, 7, 8, 10, 3

REAR STRIP GUIDE
ADJUSTMENT REQUIRED
WHEN CHANGING FROM
ONE PRODUCT TO THE
OTHER

■ DENOTES WEARING PARTS
RECOMMEND PURCHASE REPLACEMENT

THIS DRAWING IS A CONTROLLED DOCUMENT FOR AMP INC. IT IS SUBJECT TO CHANGE AND THE CONTROLLING ENGINEERING ORGANIZATION SHOULD BE CONTACTED FOR THE LATEST REVISION.

THIS APPLICATOR IS TO BE USED ON		DIST.
AMP-O-LECTRIC 1-471273-2		4
ALIGN. GA.	679597-1	
SERIAL NO.	DATE SHIPPED	DESIGNED
		3/29/95
CUSTOMER NAME AND ADDRESS		CHK'D
		4-9-95
APPLICATOR NUMBER	REV.	APP'D.
	G 566260-3	1/8
		2/10/98

THIS DRAWING IS UNCLASSIFIED DATE 11/19/01 BY AMP INCORPORATED. ALL RIGHTS RESERVED. © COPYRIGHT 1989