


## Specification Sheet

Part Number: T150XL3X2



<b>Article Number</b>	111-15504
<b>Type</b>	T150XL
<b>Color</b>	Orange (OG)
<b>Features &amp; Benefits</b>	<ul style="list-style-type: none"><li>• Heavy-duty design offers higher tensile strength.</li><li>• Buckle feature on head allows excess strap to be tucked away after installation.</li><li>• Bent tail ensures a quick and simple installation.</li></ul>
<b>Quantity Per</b>	bag
<b>Product Description</b>	Heavy-Duty T-Series Cable Ties feature inside serrations to provide a positive hold on wire and cable bundles. Durable head design guarantees high tensile strength and a low insertion force. The bent tail allows quick and simple installations by hand. For high-volume applications, tensioning tools are available to ensure consistent and safe installation.
<b>Short Description</b>	Heavy Duty Cable Tie, 43.1" Long, UL Rated, 175lb Tensile Strength, PA66, Orange, 25/pkg

Global Part Name

T150XL-PA66-OG

Minimum Tensile Strength (Imperial)

175.0

Minimum Tensile Strength (Metric)

780.0

Length L (Imperial)

43.1

Length L (Metric)

1095.0

Identification Plate Position

none

Releasable Closure

No

Tie Closure

plastic pawl

Variant

Inside Serrated

Width W (Imperial)

0.35

Width W (Metric)

8.9

Bundle Diameter Min (Imperial)

6.0

Bundle Diameter Min (Metric)

152.0

Bundle Diameter Max (Imperial)

13.0

Bundle Diameter Max (Metric)

330.2

Thickness T (Metric)

2.1

<b>Material</b>	Polyamide 6.6 (PA66)
<b>Material Shortcut</b>	PA66
<b>Flammability</b>	UL 94 V2
<b>Halogen free</b>	Yes
<b>Operating Temperature (Metric)</b>	-40°F to +185°F (-40°C to +85°C)
<b>ROHS Complaint</b>	Yes
<b>Certification/Specification WEB</b>	UL-ZODZ2.E64139
<b>UL Recognized (US)</b>	Yes
<b>UL Recognized (US and Canada)</b>	Yes
<b>Package Quantity(Imperial)</b>	25
<b>Package Quantity (Metric)</b>	25
<b>Customs Number</b>	3926909987