



Specification:

- Electrical Char
Insulation Resistance: 500M Ω min. 500V DC for 1 minute
Contact Resistance: 20m Ω max.
Rating Current: 1.5A max.
Rating Voltage: 120V AC
Dielectric Voltage: 1000 Vrms at 1MA 60 sec. min.
- Physical Char
Housing: PBT Glass filled (UL 94V-0) Color: Black
Soldering Temperature: 235°C for 5 sec.
Spring Wire: 0.45mm Dia Phosphor Bronze
6 μ " Gold plating over Nickel
Temperature Range: -40°C to +85°C
Durability: 500 mating cycles min.
- Packing: Tray

RoHS compliant
Unit:mm

Scale	Free	Free	Free
TOLERANCE			
.XX	± 0.20		
.XXX	± 0.13		
.XXXX	± 0.05		
DIM	TOL		
Angle	$+0^{\circ}30'$		

Id.	Drawn	Modification	Date	Name
①	Drawn		04.08.2016	Winnie

Date	Name
04.08.2016	Winnie

Customer-No.	Name
	Winnie

Date	Name
04.08.2016	Winnie

ASSMANN WSW-Components	ASSMANN WSW-No.	Drawing-No.	Replace
	A-2014-0-4-R	ASS 7327 CO	rev00

1	2	3	4	5	6	7