

**ebm-papst St. Georgen GmbH & Co. KG**

Hermann-Papst-Str. 1

D-78112 St. Georgen

Phone +49 (0) 7724 81-0

Fax +49 (0) 7724 81-1309

info2@de.ebmpapst.com

www.ebmpapst.com

Nominal data

| Type | 8880 TV | |
|--------------------------|-------------------|------|
| Phase | | 1~ |
| Nominal voltage | VAC | 230 |
| Frequency | Hz | 50 |
| Speed (rpm) | min ⁻¹ | 1650 |
| Power consumption | W | 9.0 |
| Min. ambient temperature | °C | -10 |
| Max. ambient temperature | °C | 80 |
| Air flow | m ³ /h | 24 |
| Sound pressure level | dB(A) | 15 |

ml = Max. load · me = Max. efficiency · fa = Free air · cs = Customer specification · ce = Customer equipment
Subject to change



Technical description

| | |
|--|---|
| Weight | 0.370 kg |
| Dimensions | Ø 76 x 37 mm |
| Impeller material | Die-cast aluminum |
| Airflow direction | Exhaust over mounting bracket |
| Direction of rotation | Clockwise, viewed toward rotor |
| Storage | Sintec sleeve bearing |
| Service life L10 at 40 °C | 60000 h |
| Service life L10 at maximum temperature | 25000 h |
| Cable | With 2 leads AWG 18, TR 64 |
| Motor protection | Protected from overload by impedance protection |
| Approval | VDE, CSA, UL, CE |



Product drawing

