



SAS 26 CKT PIN	SIGNAL DESC	SIGNAL DESC	SFF-8484 PIN
B4	SGND	SGND	1
B2	Tx0+	Rx0+	2
B3	Tx0-	Rx0-	3
A4	SGND	SGND	4
A2	Rx0+	Tx0+	6
A3	Rx0-	Tx0-	5
B7	SGND	SGND	7
B5	Tx1+	Rx1+	8
B6	Tx1-	Rx1-	9
A7	SGND	SGND	10
A5	Rx1+	Tx1+	12
A6	Rx1-	Tx1-	11
NC	SGND	SGND	13
		NC	14
		NC	15
		NC	16
		NC	17
		NC	18
		NC	19
NC	SGND	SGND	20
B8	Tx2+	Rx2+	21
B9	Tx2-	Rx2-	22
B10	SGND	SGND	23
A8	Rx2+	Tx2+	25
A9	Rx2-	Tx2-	24
A10	SGND	SGND	26
B11	Tx3+	Rx3+	27
B12	Tx3-	Rx3-	28
B13	SGND	SGND	29
A11	Rx3+	Tx3+	31
A12	Rx3-	Tx3-	30
A13	SGND	SGND	32

P/N	DESC	LENGTH
74558-0001	SAS 26 CKT TO INTERNAL SFF-8484	0.5M
74558-0002	SAS 26 CKT TO INTERNAL SFF-8484	1.0M

- NOTES:
1. LENGTH- SEE TABLE
  2. ELECTRICAL PERFORMANCE PER SERIAL ATTACH SCSI
  3. ASSEMBLY IS TO BE RoHS COMPLIANT BY JULY 1, 2005
  4. SFF-8484 MATES WITH:  
RIGHT ANGLE: 87861  
VERTICAL: 87862
  5. 1-PASS 4X EXTERNAL (UNIVERSAL KEY) MATES WITH:  
RECEPTICAL: 75586-0004  
EMI GUIDE HOUSING ASSEMBLY: 74548-0103 TO 0111,  
74548-0203 TO 0211
  6. LABEL  
MOLEX P/N  
MOLEX  
MADE IN CHINA  
YDDD

SGND= SIGNAL GROUND  
NC= NOT CONNECTED

ENTER DESCRIPTION EC NO: USY2008-0160 DRWN: PYSYWSA 2007/11/14 CHKD: 2007/11/15 APPR: DDOYE 2007/11/26 REV DESCRIPTION	QUALITY SYMBOLS	GENERAL TOLERANCES (UNLESS SPECIFIED)	DIMENSION STYLE	SCALE	DESIGN UNITS	THIRD ANGLE PROJECTION	
	$\nabla=0$ $\nabla=0$	mm INCH 4 PLACES ± --- ±.0002 3 PLACES ± --- ±.005 2 PLACES ± 0.13 ±.01 1 PLACE ± 0.25 ± --- ANGULAR ±1/2°	MM/IN	1:1	METRIC	THALL DATE 2005/05/19 CHECKED BY DATE 2005/05/19 APPROVED BY DATE 2005/05/19 DDOYE	TITLE SAS 26 CKT TO INTERNAL SFF-8484 PLUG TO PLUG
		DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS	SEE TABLE	MATERIAL NO.	DOCUMENT NO.	MOLEX INCORPORATED SD-74558-100	
			SIZE B	THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION			SHEET NO. 1 OF 1