

Linearer Hub  
Straight action principle

Entriegelbare Zwangssperre  
Ratchet release

Ergonomisch gestylte Softhandgriffe  
Farbe: SIGNALGELB (RAL 1003)  
Ergonomic soft grips  
color: yellow (RAL 1003)



Kontaktpositionierung mit Anschlag  
Contact positioning with locator

Präzise geschliffene Profile  
Precisely ground profiles

Voll recyclefähig  
Fully recyclable

Anwendungsbereich: 'HARTING RJ Industrial® Gigalink Steckverbinder'  
Application range: 'HARTING RJ Industrial® Gigalink connectors'

Leiterquerschnitt: AWG 26/7-24/7 (0,14-0,23mm<sup>2</sup>)  
Cross section range: AWG 26/7-24/7 (0,14-0,23mm<sup>2</sup>)

 All Dimensions in mm Original Size DIN A 4			Techn. Character.			Nicht tolerierte Maße / Free size tolerances	
				Dat.	Name	Maßstab / Scale	
			Detail.	23.07.04	Wie	1:1	
			Insp.	23.07.04	Wae		
			Stand.				
32405	23.11.04	Wie	HARTING Electronics GmbH & Co. KG D. 39239 ESSELKAMP			RJ Industrial Gigalink Crimpzange RJ Industrial Gigalink crimp tool	
32096						TB 09 45 800 0500	