

Specification Sheet

Part Number: 170-03107



Plenum Rated Expandable Braided Sleeving (Halar), .75" Dia, WH, 75ft/reel

Article Number	170-03107
Type	BSHLR3410
Color	White (WH)
Features & Benefits	<ul style="list-style-type: none">• Meets UL 2024 and NFPA 262 specifications meets requirements for use in plenum applications.• Technically advanced monofilament material is rated as low smoke, flame resistant and can withstand exposure to Cobal 60 radiation.• Exceeds requirements of FMVSS 302 as well as aviation industry requirements of FAR25.
Quantity Per	reel
Product Description	Halar self-extinguishing sleeving is used where flammability, high temperature endurance and low outgassing are the primary concern.
Short Description	Plenum Rated Expandable Braided Sleeving (Halar), .75" Dia, WH, 75ft/reel

Global Part Name

BSHLR3410-PA66E/CTFE-WH

Length L (Imperial)

75.0

Length L (Metric)

22.9

Bundle Diameter Min (Imperial)

0.5

Bundle Diameter Min (Metric)

12.7

Bundle Diameter Max (Imperial)

1.25

Bundle Diameter Max (Metric)

31.8

Diameter D (imperial)

0.75

Diameter D (metric)

19.1

Nominal Diameter (Imperial)

3/4

Nominal Diameter (Metric)

19.1

Material

Ethylene Chlorotrifluoroethylene (E/CTFE)

Material Shortcut

PA66E/CTFE

Flammability

FAR 25 UL VW-1

Halogen free

No

Operating Temperature (Metric)	-103°F to +302°F (-75°C to +150°C)
Reach Complaint(Article 33)	Yes
ROHS Complaint	Yes
Certification/Specification WEB	UL UL 1441 UL ANSI/UL 746B UL UL 746A UL 2024
UL Recognized (US)	Yes
UL Recognized (US and Canada)	Yes
Package Quantity(Imperial)	75
Package Quantity (Metric)	22.86
Customs Number	3926909987
Weight (Metric)	0.58
Weight (Imperial)	1.28