



Directive 2002/95/EC RoHS compliant

plating pos. 2		part no.
GOLD FLASH over NICKEL		132A13039X
min. 20µin HARD GOLD over min. 50µin NICKEL		132B13039X
min. 30µin HARD GOLD over min. 50µin NICKEL		132C13039X

pos	qty	description	material	plating
3	1	RETAINING RING	COPPER ALLOY	NICKEL PLATED
1	1	MATING SIDE	COPPER ALLOY	SEE PARTLIST
2	1	REAR SIDE	COPPER ALLOY	TIN PLATED

partlist					scale: 8:1			
THIS DRAWING MAY NOT BE COPIED OR REPRODUCED IN ANY WAY, AND MAY NOT BE PASSED ON TO A THIRD PARTY WITHOUT WRITTEN PERMISSION. OWNERSHIP AND COPYRIGHT OF CONEC GmbH DO NOT ALTER CAD DRAWING BY HAND					tolerance	ISO 2768-m		
					dim. in mm		material: SEE PARTLIST	
					date	name	title:	
					drawn	23.03.98	Barcinski	HIGH POWER CONTACT FEMALE
appd.	23.03.98	Mickenbecker	SOLDER PIN 90°, d=3.75, 40A					
norm			D-SUB COMBINATION					
d-old			dwg no:					
1 x b	A4680	06.03.2013	K.H.	13K11F8A	DIN-A3			
a	Original				sh: 1			
rev.	description	date	name	CONEC	part no: SEE TABLE			