

## Housing - HC-D 25-SML-57/M2PG21 - 1677584

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://download.phoenixcontact.com>)

Box mounting base, with single locking latch, height 57 mm, with screw connection, 2x Pg21



### Key commercial data

|                                      |            |
|--------------------------------------|------------|
| Packing unit                         | 1 PCE      |
| Weight per Piece (excluding packing) | 265.48 GRM |
| Custom tariff number                 | 85389099   |
| Country of origin                    | Germany    |

### Technical data

#### Dimensions

|                         |                           |
|-------------------------|---------------------------|
| Height                  | 57 mm                     |
| Width                   | 50 mm                     |
| Length                  | 109.5 mm                  |
| Wrench size, union nut  | 28 mm                     |
| External cable diameter | 10 mm ... 19 mm (Cable 1) |
|                         | 10 mm ... 19 mm (Cable 2) |

#### Ambient conditions

|                                      |                   |
|--------------------------------------|-------------------|
| Degree of protection of housing (IP) | IP65              |
| Ambient temperature (operation)      | -40 °C ... 125 °C |

#### General

|                    |                                 |
|--------------------|---------------------------------|
| Note               | For contact inserts HC-D25, A16 |
| Design             | D25                             |
| Housing type       | Box mounting bases              |
| Locking type       | With single locking latch       |
| No. of cable exits | 2                               |

# Housing - HC-D 25-SML-57/M2PG21 - 1677584

## Technical data

### General

|                              |                     |
|------------------------------|---------------------|
| Cable exit                   | Lateral             |
| Screw connection             | With                |
| Type of the screw connection | 2x Pg21             |
| Housing material             | Aluminum die-cast   |
| Housing surface material     | Powder-coated, gray |
| Cable gland material         | Nickel-plated brass |
| Cable seal material          | NBR                 |
| Material lock                | Steel, galvanized   |

## Classifications

### eCl@ss

|            |          |
|------------|----------|
| eCl@ss 4.0 | 27140816 |
| eCl@ss 4.1 | 27140816 |
| eCl@ss 5.0 | 27143424 |
| eCl@ss 5.1 | 27143424 |
| eCl@ss 6.0 | 27143424 |
| eCl@ss 7.0 | 27440209 |
| eCl@ss 8.0 | 27440209 |

### ETIM

|          |          |
|----------|----------|
| ETIM 2.0 | EC000437 |
| ETIM 3.0 | EC000437 |
| ETIM 4.0 | EC000437 |
| ETIM 5.0 | EC000437 |

### UNSPSC

|               |          |
|---------------|----------|
| UNSPSC 6.01   | 31261502 |
| UNSPSC 7.0901 | 31261502 |
| UNSPSC 11     | 31261502 |
| UNSPSC 12.01  | 31261502 |
| UNSPSC 13.2   | 31261502 |

## Approvals

### Approvals

---

# Housing - HC-D 25-SML-57/M2PG21 - 1677584

## Approvals

Approvals

GOST

---

Ex Approvals

---

Approvals submitted

---

## Approval details



## Drawings

Dimensioned drawing

