

APPLICATOR PARTS LIST				TYPE 180 DIA. PLUG SIDEWISE RECPT. BENT UP 90°				AMP INCORPORATED HARRISBURG, PENNA.			
NO.	DESCRIPTION	REQ.	PART NO.	NO.	DESCRIPTION	REQ.	PART NO.	CRIMPING DATA			TERMINALS
1	■ WIRE CRIMPER	1	4456106-7	42	SHEAR PLATE LEFT	1	811855-1	TO APPLY TERMINAL			42700-K
2	■ INS. CRIMPER	1	810107	43	SHEAR BLOCK RIGHT	1	386372	WIRE SIZE	CRIMP HEIGHT		
3	■ ANVIL	1	803159-1	44	■ FLOATING SHEAR	1	465406	20	.057		
4	ANVIL SPACER	1	803156-1	45	RETAINING PLATE FRONT	1	811714-3	18	.061		
5	■ SHEAR BLADE			46	RETAINING PLATE REAR	1	810822-1	16	.069		
6	■ REAR SHEAR PLATE			47	SPRING, SHEAR RETURN	1	374322	CRIMP	SIZE	TYPE	FEED
7	SHEAR BLADE SPACER			48	SHEAR DEPRESSOR	1	453302-3	WIRE	.090	"F"	
8	■ FRONT SHEAR PLATE			49	KEY, SHEAR RETAINER	1	386358	INSUL.	.155	0"	.740
9	REAR ANVIL SPACER PLT.			50				SLEEVED			
10	FRONT STRIP HOLD	1	811593-1	51				INSULATION RANGE	WIRE RANGE		
11	TOOL SPACER	1	372166	52				.100-140	20-16		
12	CRIMP SPACER	1	370572	53	BENDING TOOL	1	803158-1	EXPLODED VIEW			
13	FRONT STRIP GUIDE	1	387564-3	54	LOWER BENDING TOOL*	1	803157-1	A-6002-13 (SIM.)			
14	REAR STRIP GUIDE	1	1-465440-0	55				REMARKS:			
15	RAM	1	473699	56	SPACER, BENDING TOOL	1	372166	*MOUNTS IN REAR OF ANVIL			
16	TOOL HOLDER			57	SPACER, STRIP GUIDE REAR	2	811527-9	TOP TOOL MOUNTING			
17	SHEAR DEPRESSOR SPACER	1	370570	58				ITEM'S: 56, 53, 11, 1, 12, 2,			
18	ADJ. BLOCK			59				17 & 48			
19	APPLICATOR MOUNT ASSY.			60							
20	BASE PLATE	1	465100	61							
21	BASE BLOCK	1	689530-1	62							
22	STRIP GUIDE PLATE	1	465414-1	63							
23	ANVIL HOLDER			64							
24	AUX. ANVIL HOLDER			65	TENSION ADJ. PLATE	1	374999				
25	STRIPPER - WIRE STOP	1	386361-1	66	MISCELLANEOUS						
26	STRIPPER MOUNT	1	388277	67	LOBRICATOR ASS'Y	1	4651842				
27	RETAINER PLATE	1	389078	68	SYNTHETIC OIL	1	22014-1				
28	STRIPPER MOUNT BRACKET	1	387715-1	69							
29	STRIPPER BUSHING	1	387049-1	70							
30	STOCK DRAG	1	336955	71							
31	STOCK DRAG HANDLE			72							
32	STOCK DRAG STD	1	374900	REV.	REVISION RECORD	DATE	BY	ECN	THIS APPLICATOR IS TO BE USED ON		
33	STOCK DRAG SPRING	1	370572	A	0150-6987-26	7-96	JSK		AMP-O-LECTRIC 1-471273-3		
34	STOCK DRAG ADJ. NUT	1	21022-3						MECH FEED		
35	FEED FINGER HOLDER	1	386942						SERIAL NO.	DATE SHIPPED	DESIGNED
36	FEED FINGER	1	386941								K. STAREN
37	FEED FINGER TIP	1	387251						CUSTOMER NAME AND ADDRESS		
38	FEED FINGER GUIDE	1	689915-2								2-B-80
39	BASE CASTING	1	570238								CHK'D.
40	GUARD	1	457665-6								APPR.
41											11/15/99

THIS DRAWING IS A CONTROLLED DOCUMENT FOR AMP INC. IT IS SUBJECT TO CHANGE AND THE CONTROLLING ENGINEERING ORGANIZATION SHOULD BE CONTACTED FOR THE LATEST REVISION.

APPLICATOR NUMBER A 566303-1 SHEET 1 OF 2

