


CPI1008J4R7R-10

UNCONTROLLED DOCUMENT

PHYSICAL DIMENSIONS:



A	2.50 [.098]	\pm	0.20[.008]
B	2.00 [.079]	\pm	0.20[.008]
C	0.90 [.035]	\pm	0.10[.004]
D	0.60 [.024]	\pm	0.20[.008]




ELECTRICAL CHARACTERISTICS:			
	L (μ H) @ 1MHz \pm 20%	DCR (Ω) \pm 25%	I (Max)
Nom	4.70	0.2000	
Min	3.76	0.1500	
Max	5.64	0.2500	1100mA

NOTES: UNLESS OTHERWISE SPECIFIED

1. TAPED AND REELED per CURRENT EIA SPECIFICATIONS 7" REELS, 3000 PCS/REEL, EMBOSSED PLASTIC TAPE.
2. TERMINATION FINISH IS 100% MATTE Sn OVER Ni.
3. COMPONENTS SHOULD BE ADEQUATELY PREHEATED BEFORE SOLDERING.
4. I (MAX.) IS BASED ON THE MAXIMUM SUSTAINED CURRENT APPLIED WHILE MAINTAINING A MAXIMUM TEMPERATURE RISE OF 40°C OVER AMBIENT.
5. OPERATION TEMPERATURE TEMP: -55°C~+125°C (INCLUDING SELF-HEATING)




LAND PATTERNS FOR REFLOW SOLDERING



(For wave soldering, add 0.763 [0.030] to this dimension)

RECOMMENDED SOLDERING CONDITIONS



DIMENSIONS ARE IN mm [INCHES].				This print is the property of Laird Tech. and is loaned in confidence subject to return upon request and with the understanding that no copies shall be made without the written consent of Laird Tech. All rights to design or invention are reserved.		Laird		
				PROJECT/PART NUMBER:		REV	PART TYPE:	DRAWN BY:
C	UPDATE PAD DIMENSION ROHS	07/08/14	QU	CPI1008J4R7R-10		C	CO-FIRE	QU
B	UPDATE LAIRD LOGO AND NOTES 5	08/05/13	QU	DATE:	03/01/11	SCALE:	NTS	SHEET:
A	ORIGINAL DRAFT	03/01/11	QU	CAD #		TOOL #		1 of 1
REV	DESCRIPTION	DATE	INT	CPI1008J4R7R-10-C				