

LOS-D

~14° diffused spot beam optimized for Osram
Oslon Square EC. 14.3 mm high assembly.

TECHNICAL SPECIFICATIONS:

Dimensions	Ø 21.6 mm
Height	14.3 mm
Fastening	glue, pin
Colour	white
Box size	480 x 280 x 300 mm
Box weight	9.1 kg
Quantity in Box	1680 pcs
ROHS compliant	yes ⓘ




MATERIAL SPECIFICATIONS:

Component	Type	Material	Colour
LXP2-D	Lens	PMMA	clear
LEILA-HLD-OSL	Holder	PC	white


PHOTOMETRIC DATA (MEASURED):





LED NF2x757A
 FWHM 13.0°
 Efficiency 91 %
 Peak intensity 11.900 cd/lm
 Required components:




LED NF2x757D
 FWHM 12.0°
 Efficiency 94 %
 Peak intensity 12.830 cd/lm
 Required components:



LED Duris S5 (2 chip)
 FWHM 14.0°
 Efficiency 91 %
 Peak intensity 11.700 cd/lm
 Required components:




LED Oslon Square EC
 FWHM 16.0°
 Efficiency 93 %
 Peak intensity 10.300 cd/lm
 Required components:



PHOTOMETRIC DATA (MEASURED):

OSRAM
Opto Semiconductors

LED Oslon SSL 150
FWHM 11.0°
Efficiency 87 %
Peak intensity 12.700 cd/lm
Required components:




OSRAM
Opto Semiconductors

LED Oslon SSL 80
FWHM 10.0°
Efficiency 93 %
Peak intensity 12.900 cd/lm
Required components:

PHOTOMETRIC DATA (SIMULATED):



LED NF2x757G
FWHM 14.0°
Efficiency 94 %
Peak intensity 11.000 cd/lm
Required components:



GENERAL INFORMATION:

NOTE: The typical beam angle will be changed by different color, chip size and chip position tolerance. The typical total beam angle is the full angle measured where the luminous intensity is half of the peak value.

MATERIALS:

As part of our continuous research and improvement processes, and to ensure the best possible quality and availability of our products, LEDiL reserves the right to change material grades without notice.

PRODUCT DATA USER AGREEMENT AND DISCLAIMER:

The measured data in the provided downloadable LEDiL Product Datasheets and Mechanical 2D-Drawings is rounded and provided as reference for planning. LEDiL Oy's optical specifications have been verified by conducting performance testing of the products in accordance with the company's quality system. The reported data are averaged results of multiple measurements with typical variation. LEDiL Oy reserves the right to without prior notification make changes and improvements to its products.

LEDiL Oy assumes neither warranty, nor guarantee nor any other liability of any kind for the contents and correctness of the provided data. The provided data has been generated with highest diligence but the provided data may in reality not represent the complete possible variation range of all intrinsic parameters. Therefore, in certain cases a deviation from the provided data could occur.

LEDiL Oy reserves the right to undertake technical changes of its products without further notification which could lead to changes in the provided data. LEDiL Oy assumes no liability of any kind for the possible deviation from any provided data or any other damage resulting from the usage of the provided data.

The user agrees to this disclaimer and user agreement with the download or usage of the provided files.

LEDiL Oy

Joensuunkatu 13
FI-24240 SALO
Finland

LEDiL Inc.

228 West Page Street
Suite D
Sycamore IL 60178
USA

Local sales and technical support

[www.ledil.com/
where_to_buy](http://www.ledil.com/where_to_buy)

Shipping locations

Salo, Finland
Hong Kong, China

Distribution Partners

[www.ledil.com/
where_to_buy](http://www.ledil.com/where_to_buy)