



PREMIUM MOBILE LOAD COIL ANTENNAS ARE INDUSTRY STANDARD

Laird Technologies' ongoing commitment to refinement in mechanical and electrical design has resulted in the most technically advanced mobile load coil antennas on the market. Exclusive features such as stainless steel whips, housings constructed with ABS material injected molded around a solid brass insert, and gold plated push pin contacts make Laird Technologies the obvious choice for quality and long lasting value for demanding mobile radio communications.


FEATURES

- $\frac{5}{8}$ " wave design for true 3 dBi performance
- High performance mobile antenna operates on a 6" diameter (min.) ground plane
- Straight stainless steel
- Easy installation with optional NMO Mounts
- 100% tested on a network

MARKETS

- Public safety
- Transportation
- Utility
- Military mobile

ANTENNA PATTERNS



**Elevation Polar Radiation Pattern
490 MHz**

SPECIFICATIONS

ELECTRICAL	
Frequency Range	490-512 MHz
Gain	3 dBi
VSWR	≤ 1.5:1
Maximum Power	100 W
Nominal Impedance	50 Ω
Polarization	Vertical
Pattern	Omnidirectional
Coaxial Cable Length & Type (For Vertical Polarization)	None
Terminations	NMO style

MECHANICAL	
Color	Black or chrome
Height	B4903: 11.625 in (29.5275 cm) B4903S: 12 in (30.48 cm)
Diameter	1.44 in (36.576 mm)
Weight	B4903: .355 lbs (5.68 oz) B4903S: .425 lbs (6.8 oz)
Material	ABS Base/Stainless Steel Rod
Mounting Information	Ground Plane

MODEL AND ORDERING INFORMATION

MODEL	DESCRIPTION	OVERALL HEIGHT
B4903	490-512 MHz, Chrome Finish	11.625 in
BB4903	490-512 MHz, Black Finish	11.625 in
B4903S	490-512 MHz, with Spring, Chrome Finish	12 in
BB4903S	490-512 MHz, with Spring, Black Finish	12 in

ANT-DS-B4903 111114

Any information furnished by Laird Inc. and its agents is believed to be accurate and reliable. All specifications are subject to change without notice. Responsibility for the use and application of Laird materials rests with the end user. Laird makes no warranties as to the fitness, merchantability, suitability or non-infringement of any Laird materials or products for any specific or general uses. Laird shall not be liable for incidental or consequential damages of any kind. All Laird products are sold pursuant to the Laird Terms and Conditions of sale in effect from time to time, a copy of which will be furnished upon request. © Copyright 2014 Laird Inc. All Rights Reserved. Laird, Laird Technologies, the Laird Logo, and other marks are trade marks or registered trade marks of Laird Inc. or an affiliate company thereof. Other product or service names may be the property of third parties. Nothing herein provides a license under any Laird or any third party intellectual property rights.