

Interface module - VIP-3/PT/HD62SUB/F - 2904275

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://download.phoenixcontact.com>)



VARIOFACE module, with push-in connections and high density D-subminiature female connector, for mounting on NS 35 rails, no. of pos.: 62

The figure shows the 44-pos. version with D-SUB plug.



Key commercial data

| | |
|--------------------------------------|---------------|
| Packing unit | 1 pc |
| Weight per Piece (excluding packing) | 293.8 GRM |
| Custom tariff number | 85369010 |
| Country of origin | United States |

Technical data

Dimensions

| | |
|--------|---------|
| Width | 113 mm |
| Height | 75.8 mm |
| Depth | 63 mm |

Ambient conditions

| | |
|---|------------------|
| Ambient temperature (operation) | -20 °C ... 50 °C |
| Ambient temperature (storage/transport) | -20 °C ... 70 °C |

General

| | |
|---|-------------|
| Nominal voltage U_N | 125 V AC/DC |
| Max. current carrying capacity per branch | 1 A |
| Number of positions | 62 |
| Status display | No |
| Mounting position | any |

Interface module - VIP-3/PT/HD62SUB/F - 2904275

Technical data

General

| | |
|------------------------|----------|
| Standards/regulations | EN 50178 |
| Pollution degree | 2 |
| Surge voltage category | II |
| Rated surge voltage | 1.2 kV |

Connection data for connection 1

| | |
|--|----------------------|
| Connection name | PCB connection |
| Connection in acc. with standard | IEC / EN |
| Connection method | Push-in connection |
| Number of positions | 26 |
| Conductor cross section solid min. | 0.14 mm ² |
| Conductor cross section solid max. | 2.5 mm ² |
| Conductor cross section stranded min. | 0.14 mm ² |
| Conductor cross section stranded max. | 2.5 mm ² |
| Conductor cross section AWG/kcmil min. | 24 |
| Conductor cross section AWG/kcmil max. | 12 |
| Stripping length | 8 mm |
| Screw thread | M3 |

Connection data for connection 2

| | |
|-----------------------|---------------------------------|
| Connection name | D-SUB connection |
| Number of connections | 1 |
| Connection method | High-density D-SUB socket strip |
| Number of positions | 62 |

Classifications

eCl@ss

| | |
|------------|----------|
| eCl@ss 4.0 | 27250313 |
| eCl@ss 4.1 | 27250313 |
| eCl@ss 5.0 | 27250313 |
| eCl@ss 5.1 | 27250313 |
| eCl@ss 6.0 | 27242608 |
| eCl@ss 7.0 | 27141152 |
| eCl@ss 8.0 | 27141152 |

ETIM

| | |
|----------|----------|
| ETIM 3.0 | EC001604 |
|----------|----------|

Interface module - VIP-3/PT/HD62SUB/F - 2904275

Classifications

ETIM

| | |
|----------|----------|
| ETIM 4.0 | EC001604 |
| ETIM 5.0 | EC001604 |

UNSPSC

| | |
|---------------|----------|
| UNSPSC 6.01 | 30211824 |
| UNSPSC 7.0901 | 39121421 |
| UNSPSC 11 | 39121421 |
| UNSPSC 12.01 | 39121421 |
| UNSPSC 13.2 | 39121421 |

Approvals

Approvals


Approvals


CSA / UL Recognized / cUL Recognized / cULus Recognized

Ex Approvals

Approvals submitted

Approval details

| | |
|---|-------|
| CSA  | |
| mm ² /AWG/kcmil | 26-14 |
| Nominal current I _N | 1 A |
| Nominal voltage U _N | 105 V |

| | |
|---|-------|
| UL Recognized  | |
| mm ² /AWG/kcmil | 26-14 |

Interface module - VIP-3/PT/HD62SUB/F - 2904275

Approvals


| | |
|--------------------|-------|
| | |
| Nominal current IN | 1 A |
| Nominal voltage UN | 125 V |

| | |
|----------------------------|-------|
| cUL Recognized | |
| mm ² /AWG/kcmil | 26-14 |
| Nominal current IN | 1 A |
| Nominal voltage UN | 125 V |

| | |
|------------------|--|
| cULus Recognized | |
|------------------|--|

Drawings

Circuit diagram



Universal circuit diagram

Schematic diagram

