

<b>APPLICABLE STANDARD</b>					
<b>RATING</b>	OPERATING TEMPERATURE RANGE	-35 °C TO +85 °C(NOTE1)		STORAGE TEMPERATURE RANGE	-10°C TO +60 °C
	VOLTAGE	250 V AC		APPLICABLE CONTACT	DF1E-*S-2.5RC
	CURRENT	AWG20-22	3A		DF1E-*EP-2.5C
		AWG24-28	1A		
AWG30		0.5A			

### SPECIFICATIONS

ITEM	TEST METHOD	REQUIREMENTS	QT	AT
------	-------------	--------------	----	----

#### CONSTRUCTION

GENERAL EXAMINATION	VISUALLY AND BY MEASURING INSTRUMENT.	ACCORDING TO DRAWING.	X	X
MARKING	CONFIRMED VISUALLY.		X	X

#### ELECTRIC CHARACTERISTICS

INSULATION RESISTANCE	500 V DC.	1000 MΩ MIN.	X	-
VOLTAGE PROOF	650 V AC FOR 1 min.	NO FLASHOVER OR BREAKDOWN.	X	-

#### MECHANICAL CHARACTERISTICS

VIBRATION	FREQUENCY 10 TO 55 Hz, SINGLE AMPLITUDE 0.75 mm.	NO DAMAGE, CRACK OR LOOSENESS OF PARTS.	X	-
SHOCK	490 m/s <sup>2</sup> DURATION OF PULSE 11 ms AT 3 TIMES FOR 3 DIRECTIONS.		X	-

#### ENVIRONMENTAL CHARACTERISTICS

RAPID CHANGE OF TEMPERATURE	TEMPERATURE -55 →5 TO 35 →+85→5 TO35°C TIME 30 →10 TO 15 →30 →10 TO 15min UNDER 5 CYCLES.	① INSULATION RESISTANCE: 1000 MΩ MIN. ② NO DAMAGE, CRACK OR LOOSENESS OF PARTS.	X	-
DAMP HEAT (STEADY STATE)	EXPOSED AT 40 ± 2 °C, 90 TO 95 %, 96 h.	① INSULATION RESISTANCE: 500 MΩ MIN. ② NO DAMAGE, CRACK OR LOOSENESS OF PARTS.	X	-

#### REMARKS

NOTE1: INCLUDE THE TEMPERATURE RISING BY CURRENT.

Unless otherwise specified, refer to JIS C 5402.

COUNT	DESCRIPTION OF REVISIONS	DESIGNED	CHECKED	DATE
△				
		APPROVED	TS. SAKATA	08.05.15
		CHECKED	TS. KUMAZAWA	08.05.15
		DESIGNED	TH. YOSHI ZAWA	08.05.15
		DRAWN	TH. YOSHI ZAWA	08.05.15

Note QT:Qualification Test AT:Assurance Test X:Applicable Test	DRAWING NO.	ELC4-161948-01
--	-------------	----------------

<b>HRS</b>	SPECIFICATION SHEET	PART NO.	DF1E-*RS/P-2.5
	HIROSE ELECTRIC CO., LTD.	CODE NO.	CL541

△ 1/1