



CIRCUIT: 4P. SPST
CONTACT CONFIGURATION

| SWITCH FUNCTION | |
|-----------------|--------|
| POS. 1 | POS. 2 |
| ON | OFF |
| 2a-1a | OPEN |

NOTES:

1. ALL DIMENSIONS IN MM [INCH]
2. GENERAL TOLERANCE: 0.0=±0.4
0.00=±0.25
3. TERM. NOS. FOR REF. ONLY
4. RATING: 10A 125V 6A 250V AC
5. CONTACT RESISTANCE: 50m ohm max.
6. INSULATION RESISTANCE: DC 500V, 100M ohm min.
7. DIELECTRIC STRENGTH: AC 1500V 1 minute

| REV. | ECN No. | DESCRIPTION | DATE | CHKD |
|------|---------|-------------------------|------|------|
| A | 10520 | RELEASED FOR PRODUCTION | | |

| TITLE | SCALE | DATE | DR | DWG | REV |
|--------------|-------|--------|----|---------|-----|
| RR34054L-GRN | 1.5:1 | 2/8/00 | MM | F030008 | A |

E-SWITCH®

THE INFORMATION CONTAINED IN THIS DOCUMENT IS PROPRIETARY TO E-SWITCH AND IS NOT TO BE COPIED OR TRANSFERRED