

SPECIFICATION CONTROL DRAWING

55PC6005

TITLE


FOUR CONDUCTOR CABLE, SHIELDED, JACKETED, 600 VOLT

Date 1-25-93

Revision

A

This specification sheet forms a part of the latest issue of Raychem Specification 55PC.



PART NUMBER	CONDUCTOR SIZE (AWG)	SHIELD SIZE (AWG)	JACKET THICKNESS (in.)			DIAMETER (in.)			WEIGHT (lbs/1000 ft.)	
			LOWER SPEC LIMIT	TARGET WALL	LOWER SPEC LIMIT	TARGET VALUE	UPPER SPEC LIMIT	TARGET VALUE	UPPER SPEC LIMIT	
			55PC6005-24*	24	38	.0060	.0080	.128	.145	.162
55PC6005-22*	22	38	.0060	.0080	.141	.160	.180	21.61	22.40	
55PC6005-20*	20	38	.0065	.0085	.161	.183	.205	29.35	30.24	
55PC6005-18*	18	38	.0065	.0085	.182	.209	.235	40.32	41.46	
55PC6005-16*	16	38	.0070	.0090	.201	.230	.259	49.42	50.78	

CONSTRUCTION DETAILS

CABLE RATINGS AND ADDITIONAL REQUIREMENTS

TEMPERATURE RATING: 150°C
 Maximum continuous conductor temperature
 VOLTAGE RATING: 600 volts (rms)
 DIELECTRIC WITHSTAND: 1500 volts (rms), 60 Hz
 CROSSLINKING PROOF TEST: 300 ± 3°C for 1 hour
 JACKET COLOR: White preferred
 JACKET ELONGATION AND TENSILE STRENGTH:
 Elongation, 50% (minimum)
 Tensile Strength, 5000 lb/in² (minimum)
 JACKET FLAWS:
 Spark Test, 1000 volts (rms), 60 Hz, 100% test
 Impulse Dielectric Test, 6.0 kV (peak), 100 % test

SHIELD COVERAGE: 85% (minimum)
 VOLTAGE WITHSTAND TEST (POST ENVIRONMENTAL):
 1000 volts (rms), 60 Hz, 1 minute

PART NUMBER:
 The ** in the part numbers above shall be replaced by a color code designator with a slash separating the component wire colors and a dash separating the component wire colors from the jacket color.
 Example: AWG 22, red, blue, yellow and green component wires; white jacket: 55PC6005-22-2/6/4/5-8

COLOR AND COLOR CODE DESIGNATORS SHALL BE IN ACCORDANCE WITH MIL-STD-681.