

## Specification Sheet

Part Number: TELS-27



Extended-Length Tie, POM, Black, 10-27" straps and 10 heads/pkg

**Article Number**

111-32110

**Type**

TELS-27

**Color**

Black (BK)

**Features & Benefits**

- Continuous strap and separate heads allow for any bundle diameter, eliminating waste.
- Smooth strap prevents cable damage.
- UV resistant materials contain an inhibitor which prolongs the life of the tie in outdoor environments.

**Quantity Per**

pack

**Product Description**

HellermannTyton's Extended Length Tie is a high tensile strength strapping system consisting of a continuous strap and separate locking head making it suitable for any bundle diameter, eliminating waste. The smooth strap and specially designed heads with stainless steel pawls, provides a strong hold on cables and wires without damage during vibration or in extreme environments. Spacers are available for dual bundle applications.

<b>Short Description</b>	Extended-Length Tie, POM, Black, 10-27" straps and 10 heads/pkg
<b>Global Part Name</b>	TELS-27-POM-BK
<b>Minimum Tensile Strength (Imperial)</b>	250.0
<b>Minimum Tensile Strength (Metric)</b>	1112.0
<b>Length L (Imperial)</b>	27.0
<b>Length L (Metric)</b>	686.0
<b>Fixation Method</b>	2 piece
<b>Identification Plate Position</b>	none
<b>Releasable Closure</b>	No
<b>Tie Closure</b>	steel pawl
<b>Variant</b>	Extended Length
<b>Width W (Imperial)</b>	0.5
<b>Width W (Metric)</b>	12.7
<b>Thickness T (Imperial)</b>	0.06
<b>Thickness T (Metric)</b>	1.52
<b>Height H (Imperial)</b>	.49
<b>Height H (Metric)</b>	12.40

<b>Material</b>	Polyacetal (POM)
<b>Material Shortcut</b>	POM
<b>Material Cable Tie</b>	Polyacetal (POM)
<b>Material Head</b>	Polyacetal (POM)
<b>Flammability</b>	UL 94 HB
<b>Operating Temperature (Metric)</b>	-40°F to +185°F (-40°C to +85°C)
<b>ROHS Complaint</b>	Yes
<b>Package Quantity(Imperial)</b>	10
<b>Package Quantity (Metric)</b>	1
<b>Customs Number</b>	3926909987