

Contact insert - RC-09S2N120000 - 1596535

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Contact insert, Number of positions: 8+1, Type of contact: Socket, Solder connection

The figure shows the 6-pos. product version



Key commercial data

| | |
|--------------------------------------|----------|
| Packing unit | 1 pc |
| Weight per Piece (excluding packing) | 5.14 GRM |
| Custom tariff number | 85389099 |
| Country of origin | Germany |

Technical data

General

| | |
|--|----------------------|
| Insertion/withdrawal cycles mechanical | 50 |
| Direction of rotation of contact chamber numbering | Counter direction |
| Coding | N |
| Contact connection method | Solder connection |
| Type of contacts | Socket |
| Number of positions | 9 |
| Contact diameter of power contacts | 2 mm |
| Litz wire cross section of power contacts min. | 0.08 mm ² |
| Litz wire cross section of power contacts max. | 2.5 mm ² |
| Nominal current per power contact at 25°C | 20 A |
| Contact diameter of signal contacts | 1 mm |
| Litz wire cross section of signal contacts min. | 0.08 mm ² |
| Litz wire cross section of signal contacts max. | 1 mm ² |
| Nominal current per signal contact at 25°C | 8 A |

Contact insert - RC-09S2N120000 - 1596535

Technical data

Material

| | |
|--------------------|-----------------------------|
| Insulator material | PBT |
| Contact material | CuZn |
| Contact surface | Nickel-plated, gold coating |

Specifications according to DIN EN 61984:2001

| | |
|--|--------|
| Nominal / operating voltage of power contacts | 300 V |
| Rated surge voltage of power contacts | 2.5 kV |
| Surge voltage category of power contacts | II |
| Pollution degree of power contacts | 3 |
| Nominal / operating voltage of signal contacts | 300 V |
| Surge voltage category of signal contacts | II |
| Pollution degree of signal contacts | 3 |

Classifications

eCl@ss

| | |
|------------|----------|
| eCl@ss 4.0 | 272607xx |
| eCl@ss 4.1 | 27260701 |
| eCl@ss 5.0 | 27260701 |
| eCl@ss 5.1 | 27260701 |
| eCl@ss 6.0 | 27260708 |
| eCl@ss 7.0 | 27440312 |
| eCl@ss 8.0 | 27440312 |

ETIM

| | |
|----------|----------|
| ETIM 3.0 | EC001121 |
| ETIM 4.0 | EC001121 |
| ETIM 5.0 | EC002641 |


UNSPSC

| | |
|---------------|----------|
| UNSPSC 6.01 | 43172015 |
| UNSPSC 7.0901 | 43201404 |
| UNSPSC 11 | 43172015 |
| UNSPSC 12.01 | 43201404 |
| UNSPSC 13.2 | 43201404 |


Drawings

Contact insert - RC-09S2N120000 - 1596535

Schematic diagram



Schematic diagram



Schematic diagram

