

## Specification Sheet

Part Number: 333-41508



Heat Shrink Tubing, 4' Long Stick, 3:1 Shrink Ratio, 1/8", 3.2/1.0 Dia, PO, Black, 20/pkg

**Article Number**

333-41508

**Type**

TFN31-ST-3/1

**Color**

Black (BK)

**Features & Benefits**

- Thin wall, flexible 3 to 1 shrink ratio material accommodates a wide range of component shapes and diameters.
- Meets UL224 VW-1 specifications, making it ideal for high heat applications (excludes clear tubing).
- Polyolefin material provides excellent insulation and mechanical strength with good resistance to solvents, oils and fuels.
- Available in bulk reels, sticks and convenience bags (HIS-3 bags), for small to large volume applications.

**Quantity Per**

lengths

**Product Description**

TFN31 series heat shrink tubing features a flexible, thin wall and highly flame retardant polyolefin material with a higher operating temperature range than general-use heat shrink tubing. and offers good resistance to solvents, oils and fuels. The 3 to 1 shrink ratio accommodates a variety of component shapes and sizes. TFN31 tubing is available in bulk reels, sticks and convenience bags (HIS-3 bags), for projects of all sizes.

**Short Description**

Heat Shrink Tubing, 4' Long Stick, 3:1 Shrink Ratio, 1/8", 3.2/1.0 Dia, PO, Black, 20/pkg

**Global Part Name**

TFN31-ST-3/1-PO-X-BK

**Length L (Metric)**

1.22

**Variant**

Thin-Wall

**Nominal Diameter (Imperial)**

1/8

**Nominal Diameter (Metric)**

3

**Wall Thickness WT (Imperial)**

.022

**Wall Thickness WT (Metric)**

0.55

**Material**

Polyolefin, cross-linked (PO-X)

**Material Shortcut**

PO-X

**Flammability**

UL 224 VW-1

**Halogen free**

No

<b>Operating Temperature (Metric)</b>	-67°F to +275°F (-55°C to +135°C)
<b>Reach Complaint(Article 33)</b>	Yes
<b>ROHS Complaint</b>	Yes
<b>Certification/Specification WEB</b>	UL   ANSI/UL 224 CSA   C22.2 no. 198.1-06
<b>UL Recognized (US)</b>	Yes
<b>UL Recognized (US and Canada)</b>	Yes
<b>Package Quantity(Imperial)</b>	20
<b>Package Quantity (Metric)</b>	20
<b>Customs Number</b>	3926909987