

MSD INC.

ENGINEERING DATA SHEET

RELAY TYPE: **FCA-325-3305L** COMPUTER PART No. **9383537**



TEST PROCEDURE

CUSTOMER/SPECIFICATION: **M83536/33-005U** REV **NONE**

MSDP-790

TEST REQUIREMENTS

±10%
 COIL RES.: 290 OHMS OPERATE TIME: 15 mS MAX RELEASE TIME: 15 mS MAX
 CONTACT MAKE BOUNCE: 1.0 mS MAX N.O. BREAK BOUNCE: 0.1 mS MAX
 CONTACT STABILIZATION TIME: 2.5 mS MAX RATED COIL VOLTAGE: 28 Vdc
 CONTACT VOLTAGE DROP: MFG TEST: 0.5 mV @ 100 mA - 5 Vdc
 FINAL TEST: 60 mV @ 10 A - 28 Vdc
 HI-POT: 1250 Vrms ALL POINTS, EXCEPT 1000 Vrms COIL TO CASE
 INSULATION RESISTANCE: 100 MEGOHMS MIN @ 500 Vdc
 VIBRATION: MIL-STD-202, METHOD 204 (20 G'S / 57-3000 HZ)
 SEAL TEST: 1 x 10⁻⁸ MAX LEAK RATE COIL TRANSIENT SUPPRESSION: 42 Vdc MAX
 OTHER: _____



Prepared By: Date		Approved By: Date	
LES WYNNE 3-18-96		<i>John Lynch</i> 3-18-96	
Rev	ECN No.	Date	
A	96-065	3-18-96	

SPECIAL INSTRUCTIONS