



- Notes
- ① Plating (ref. No. ③, ④)  
 Contact area : Gold 0.2μm min  
 Others : Gold and nickel  
 Under plating : Nickel 2μm min
  - ② The recommended clamp torque of ref. No. ⑩, ⑫ to be 1.5 to 2 N·m.  
 Thread locker to the threaded portion of ref. No. ① is recommended to prevent ref. No. ①, ⑨ from loosening.  
 Recommended thread locker : LOCTITE 263, HENKEL JAPAN LTD.
  - ③ The recommended clamp torque of ref. No. ⑰ to be 0.8 to 1 N·m.  
 Thread locker and lock primer to the threaded portion M12.5 × 0.75 of ref. No. ⑫ is recommended to prevent ref. No. ⑫ from loosening.  
 Recommended thread locker and lock primer : LOCTITE 263, LOCK PRIMER 7649, HENKEL JAPAN LTD.
  - ④ Fasten ref. No. ⑲ to the cable with the cable crimping tool.  
 And make ref. No. ⑲ contact with ref. No. ⑭ (Refer to Fig.1).  
 Refer to the technical specification ETAD-C0404 for details.
  - ⑤ Applicable cable crimping tool : LF-TC-01 (CL-150-0234-6) (The hole diameter for crimping: φ7.9)  
 Applicable cable assembly fixture : LF10BP-T01 (CL150-0235-9)
  - ⑥ The recommended clamp torque of ref. No. ⑱ to be 0.12 to 0.15 N·m, and opposite side distance is 0.889mm.  
 Thread locker and lock primer to the threaded portion of ref. No. ⑱ is recommended to prevent ref. No. ⑱ from loosening.  
 Recommended thread locker and lock primer : LOCTITE 263, LOCK PRIMER 7649, HENKEL JAPAN LTD.
  - ⑦ Rotation examples of ref. No. ⑤, ⑨ and ⑩ to ① are shown.  
 and rotation examples of ref. No. ⑫, ⑰ to ⑨ are shown.
  - ⑧ The cable pull and twisting strength and other characteristics may differ,  
 depending on the cable structure, please confirm before the use.

10	Brass	Nickel plating			
9	Brass	Nickel plating	19	Brass	Nickel plating
8	Stainless steel		18	Stainless steel	Hex socket set screw Dimple M2×0.4×2
7	Chloroprene rubber	(Black)	17	PPS	(Natural, Brown)
6	Stainless steel		16	Polyamide	(Natural, Minky white)
5	Zinc alloy	Nickel plating	15	Chloroprene rubber	(Black)
4	Copper alloy	①	14	Phosphor bronze	Nickel plating
3	Copper alloy		13	Chloroprene rubber	(Black)
2	PPS	(Black) UL94V-0	12	Zinc alloy	Nickel plating
1	Brass	Nickel plating	11	Stainless steel	
NO.	MATERIAL	FINISH . REMARKS	NO.	MATERIAL	FINISH . REMARKS

UNITS	SCALE	COUNT	DESCRIPTION OF REVISIONS	DESIGNED	CHECKED	DATE
mm	2 : 1	△				
HIROSE ELECTRIC CO., LTD.			APPROVED : HY. KOBAYASHI 18.02.19 CHECKED : HY. KOBAYASHI 18.02.19 DESIGNED : TY. SUZUKI 18.02.19 DRAWN : HM. SAITO 18.02.07	DRAWING NO. EDC-119019-31-00 PART NO. LF10WBLP-12SA(31) CODE NO. CL136-0013-0-31		