

**Cable glands
VG M40-EXE MS**

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 16
D-32758 Detmold
Germany
Fon: +49 5231 14-0
Fax: +49 5231 14-292083
www.weidmueller.com



Brass cable glands for use in ATEX areas

General ordering data

Order No.	1737250000
Type	VG M40-EXE MS
Version	Cable gland, Brass, nickel-plated, External thread: M 40
GTIN (EAN)	4008190956721
Qty.	10 pc(s).

**Cable glands
VG M40-EXE MS**

Weidmüller Interface GmbH & Co. KG
 Klingenbergstraße 16
 D-32758 Detmold
 Germany
 Fon: +49 5231 14-0
 Fax: +49 5231 14-292083
 www.weidmueller.com

Technical data

Dimensions and weights

Length	38 mm	Net weight	268.2 g
--------	-------	------------	---------

Approvals

Approval for cable gland	Ex e II, II 2 GD
--------------------------	------------------

General information

AF size 1	52 mm	Cable gland	metric
Clamping range, max.	33.5 mm	Clamping range, min.	24.5 mm
External thread	M 40	Length of thread	11 mm
Material	Brass, nickel-plated	O-Ring	NBR
Operating temperature range, max.	100 °C	Operating temperature range, min.	-40 °C
Pitch of thread	1.5	Protection degree with GWDR	IP 68 - 5 bar (30 min.)
Seal insert	CR	Sealing	NBR
Torque for cap nut, max.	135 Nm	Torque for cap nut, min.	135 Nm
Torque for connecting adapter, max.	27.5 Nm	Torque for connecting adapter, min.	27.5 Nm

Classifications

ETIM 2.0	EC000441	ETIM 3.0	EC000441
UNSPSC	30-21-18-01	eClass 4.1	27-14-12-11
eClass 5.1	27-14-91-11	eClass 6.2	27-14-91-11
eClass 7.1	27-14-91-11		

Approvals

Approvals



ROHS	Conform
------	---------