REV.	DATE	DESCRIPTION
NC	08/05/99	INITIAL RELEASE







RECOMMENDED CABLE STRIPPING DIM'S





	DESCRIPTION	MATERIAL	FINISH
1	BODY/BARREL	BRASS	NICKEL
2	INSULATOR	TEFLON	NATURAL
3	CONTACT PIN	BRASS	GOLD
4	FERRULE	COPPER	NICKEL
5	HEAT SHRINK TUBE		
6			
7			
8			

UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN MILLIMETERS

DIMENSIONS IN [ ] ARE IN INCHES FOR CUSTOMER REFERANCE ONLY

UNLESS OTHERWISE SPECIFIED TOLERANCES FOR MILLIMETERS ARE:

0.5–6 = ± 0.2
6–30 = ± 0.4
30–120 = ± 0.6
120–315 = ± 1
315–1000 = ± 1.6
1000–2000 = ± 2.4

DO NOT SCALE DRAWING

APPROVALS		DATE
DRAWN	G.R.S.	08/05/99
CHECKED		
ISSUED		

Connector Corporation

TITLE: SMB R/A CRIMP JACK (FOR RG–174/U, 188A/U, 316/U CABLE)

SIZE	FSCM NO.	DWG. NO.	REV.
A	99001	142251.DWG	NC

SCALE	PART NO.	SHEET
NA	142251	1 OF 1