

## Specification Sheet

Part Number: 170-03065



Braided Sleeving, Aluminum Laminated Fiberglass, 1.75" Dia, AL/GF, Silver, 50 ft/reel

**Article Number**

170-03065

**Type**

BSHTTST134SR

**Color**

Silver (SR)

**Features & Benefits**

- A layer of aluminum provides protection from chemicals, scraping, cuts and abrasion.
- Additional layer also provides insulation barrier for vulnerable wires and cables within high temperature environments.
- Cuts with ordinary scissors for fast, easy application.

**Quantity Per**

reel

**Product Description**

A tubular shaped sleeving product that combines the protection of bonded aluminum and fiberglass into a single solution that is able to deflect radiant heat away from sensitive components inside the tube.

**Short Description**

Braided Sleeving, Aluminum Laminated Fiberglass, 1.75" Dia, AL/GF, Silver, 50 ft/reel

**Global Part Name**

BSHTTST134SR-AL/GF-ML

**Length L (Imperial)**

50.0

**Length L (Metric)**

15.2

**Bundle Diameter Min (Imperial)**

0.1

**Bundle Diameter Min (Metric)**

2.54

**Bundle Diameter Max (Imperial)**

1.687

**Bundle Diameter Max (Metric)**

42.8

**Diameter D (imperial)**

1.25

**Diameter D (metric)**

31.8

**Nominal Diameter (Imperial)**

1-3/4

**Nominal Diameter (Metric)**

44.5

**Wall Thickness WT (Imperial)**

0.025

**Wall Thickness WT (Metric)**

0.64

**Material**

Glass Fiber (GF) Aluminum (AL)

**Material Shortcut**

GF AL

<b>Flammability</b>	Non-Flammable
<b>Halogen free</b>	Yes
<b>Operating Temperature (Metric)</b>	-76°F to +491°F (-60°C to +255°C)
<b>Reach Complaint(Article 33)</b>	Yes
<b>ROHS Complaint</b>	Yes
<b>Package Quantity(Imperial)</b>	50
<b>Package Quantity (Metric)</b>	15.24
<b>Customs Number</b>	7019901000
<b>Weight (Metric)</b>	1.68
<b>Weight (Imperial)</b>	3.70