

used for:

2 x JACK SCREW



2 x KNURLED NUT




2 x COUNTERSUNK-HEAD SCREW



2 x PAN-HEAD SCREW



1 x CABLE STRAIN RELIEF



No. of pos.	A	B	C	D	E	F	Part No. Bulk package	Part No. Single package
15	42.3	33.3	37.0	39.75	14.5	10.0	165X14169X	165X14169XE
25	56.0	47.0	37.0	39.75	14.5	10.5	165X14179X	165X14179XE
37	72.5	63.5	37.0	39.75	14.5	10.5	165X14189X	165X14189XE
50	67.0	61.1	49.1	51.40	19.8	14.0	165X14199X	165X14199XE

HOOD ASSEMBLY CONSISTS OF:

1. HOOD: ABS UL 94 V-0; GREY
2. JACK SCREW: BRASS; NICKEL PLATED
3. KNURLED NUT: BRASS; NICKEL PLATED
4. COUNTERSUNK-HEAD SCREW: STEEL; NICKEL PLATED
5. PAN-HEAD SCREW: STEEL; NICKEL PLATED
6. CABLE STRAIN RELIEF: STEEL; NICKEL PLATED

Directive 2002/95/EC RoHS compliant

THIS DRAWING MAY NOT BE COPIED OR REPRODUCED IN ANY WAY, AND MAY NOT BE PASSED ON TO A THIRD PARTY WITHOUT WRITTEN PERMISSION.
 OWNERSHIP AND COPYRIGHT OF CONEC GmbH
 DO NOT ALTER CAD DRAWING BY HAND

tolerance		dim. in mm	
2011	date	name	
drawn	20.01.	Henneboel	
appd.	20.01.	Fischer	
norm			
d-old			
a	Origin		
rev.	description	date	name



scale:	1:1
material:	SEE NOTES
title:	PLASTIC HOOD 15pos. / 25pos. / 37pos. / 50pos. with straight cable exit and jack screws
dwg no:	16K1A2762
part no:	SEE TABLE
DIN-A	4
sh:	1/1