





Features

- Compatible with all inserts size Han® 3 A
- High robustness via an internal locking mechanism
- Optimal EMC properties
- High quality industrial design
- With entry for M20 or M25 cable glands




Technical characteristics

Material	zinc die-cast
Surface	
Hood	Epoxy powder paint
Housings bulkhead mounting	zinc passivation
Locking element	PA / stainless steel
Limiting temperatures	-40 °C ... +125 °C
Un-/Locking temperatures	-10 °C ... +85 °C
Degree of protection acc. to DIN EN 60 529	
for coupled connector	IP 65 / IP 67
Tightening torque	
M3 fixing screw	1 Nm

Hoods Han-Yellock®

Identification	Part number	Cable entry	Drawing	Dimensions in mm
<p>Hood top entry Han-Yellock® 10</p> 	<p>11 20 003 1400 11 20 003 1401</p>	<p>M20 M25</p>		
<p>Hood angled entry Han-Yellock® 10</p> 	<p>11 20 003 1600 11 20 003 1601</p>	<p>M20 M25</p>		

Housings Han-Yellock®

Identification	Part number	Cable entry	Drawing	Dimensions in mm
<p>Housings bulkhead mounting</p> <p>Han-Yellock® 10</p> 	<p>11 20 003 0300</p>			
<p>Han-Yellock® 10</p> 	<p>11 20 003 0800</p>		