

	1	2	3	4	5	6	7																																																		
A																																																									
B																																																									
C																																																									
D																																																									
E	<p>Technical Specification:</p> <ul style="list-style-type: none"> Rated current: 5 A (RT) Nominal voltage: 50 VAC / 120 VDC AC Test voltage: 500 V Operating temperature: -50 to 100°C Mating cycles: min. 3 Pitch: 2.54mm Contact resistance: < 10mOhm Contact material: Bronze, gold flash plated Push-on force: ~4-5 N/contact Withdrawal force: ~2-3 N/contact Degree of protection: IP 00 Insulation body: TPE Flammability category: UL 94 V-0 Shore Hardness: 70A +-5 																																																								
F	<p>Packing : Bulk (1250 pcs/bag)</p>																																																								
G	<p>ROHS compliant</p> <p>Unit:mm</p> <table border="1"> <thead> <tr> <th>Scale</th> <th>Free</th> <th></th> <th></th> <th></th> <th></th> <th></th> </tr> </thead> <tbody> <tr> <td>TOLERANCE</td> <td>±0.50</td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>X.</td> <td>±0.30</td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>X.X</td> <td>±0.20</td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>X.XXX</td> <td>±0.15</td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>DIM</td> <td>TOL</td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>Angle</td> <td>±5°</td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> </tbody> </table>							Scale	Free						TOLERANCE	±0.50						X.	±0.30						X.X	±0.20						X.XXX	±0.15						DIM	TOL						Angle	±5°						
Scale	Free																																																								
TOLERANCE	±0.50																																																								
X.	±0.30																																																								
X.X	±0.20																																																								
X.XXX	±0.15																																																								
DIM	TOL																																																								
Angle	±5°																																																								
H	<table border="1"> <thead> <tr> <th>Id.</th> <th>Modification</th> <th>Date</th> <th>Name</th> <th>Date</th> <th>Name</th> </tr> </thead> <tbody> <tr> <td>①</td> <td>updated of technical specification</td> <td>14.08.2013</td> <td>A. Plate</td> <td></td> <td></td> </tr> <tr> <td>②</td> <td>Drawn</td> <td>28.05.2013</td> <td>Winnie</td> <td></td> <td></td> </tr> </tbody> </table>							Id.	Modification	Date	Name	Date	Name	①	updated of technical specification	14.08.2013	A. Plate			②	Drawn	28.05.2013	Winnie																																		
Id.	Modification	Date	Name	Date	Name																																																				
①	updated of technical specification	14.08.2013	A. Plate																																																						
②	Drawn	28.05.2013	Winnie																																																						
<p>ASSMANN</p> <p>Wsw components</p>					<p>Customer-No.</p> <p>ASSMANN WSW-No.</p> <p>ABTB-300-040B</p>		<p>Drawing-No.</p> <p>ASS 5718 CO</p> <p>rev01</p>																																																		
<p>ASSMANN</p> <p>Wsw components</p>					<p>Date</p> <p>28.05.2013</p> <p>Winnie</p>		<p>Replace</p> <p>SHEET 1</p>																																																		