

## SUMMARY

### # Wires

Low	8
High	0
Coax	0
Triax	0
Quad	0
Fiber	0
Fluidic	0



### Download

[Request a quote](#)

[Catalog](#)

### Series

Termination type	Male solder
IP rating	50
Cable Ø	5.30 - 6.50 mm
Matching parts	xxx

## TECHNICAL DETAILS

### Mechanics

Shell Style/Model	XA*: Straight plug, key (N) or keys (P, S and T), with blue cable collet
Keying	3 key (alpha=30, plug: male contacts, receptacle: female contacts)
Housing Material	
Cable Fixing	∅ 5.3 - 6.5 mm
Variant	A : Blue collet nut

### Performance

Configuration	M08 : 8 Low Voltage
Insulator	L: PEEK
Rated Current	

### Specifications

Test voltage (kV rms) Contact-contact:	1.5
Air clearance min. (mm) or Creepage distance min. (mm):	0.75


### Others

F ret (average):	130 N
Working temperature:	-50 deg C to + 170 deg C
IP Rating:	50

---

# DRAWINGS

## Draws



## Dimensions

	A	L
mm.	16.5	46
in.	0.65	1.81

---

# RECOMMENDED BY LEMO

## Tools

None

## Cables

26.308.PVB.63N.02	PVC	Black	
BELDEN 9421	PVC	Grey	