



- NOTES
- ① The recommended tightening torque of Ref No. ⑥ : 3 to 3.5 N·m.
 - ② The recommended tightening torque of Ref No. ⑩ : 0.2 to 0.25 N·m.
 - ③ One example of the rotation of REF. No. ⑥ to REF. No. ① is shown.
 - ④ LOCTITE 263 HENKEL JAPAN or equivalent is recommended to prevent REF. No. ①, ⑥ and ⑩ for loosening.
 - ⑤ This products to be used with cable clamp, JR16WCC-※
 ※Designate diameter(mm) of applicable cable.
 - ⑥ The cable pull and twisting strength, waterproof tightness and other characteristics may differ, depending on the cable structure.
 Please confirm before the use.

| NO. | MATERIAL | FINISH . REMARKS | NO. | MATERIAL | FINISH . REMARKS |
|-----|---------------------|------------------------|-----|--------------------------------|------------------------------------|
| 5 | PHOSPHOR BRONZE | NICKEL PLATING | 10 | STAINLESS STEEL | HEX SOCKET SET SCREW HEX : 1.27 |
| 4 | PHENOL FORMALDEHYDE | (BLACK) UL94V-0 | 9 | ACRYLONITRILE BUTADIENE RUBBER | (BLACK) |
| 3 | PHENOL FORMALDEHYDE | (BLACK) UL94V-0 | 8 | ACRYLONITRILE BUTADIENE RUBBER | (BLACK) |
| 2 | COPPER ALLOY | SILVER PLATING 3µm min | 7 | BRASS | BLACK CHROME PLATING |
| 1 | ALUMINUM ALLOY | BLACK CHROME PLATING | 6 | BRASS | BLACK CHROME PLATING |

| UNITS | SCALE | COUNT | DESCRIPTION OF REVISIONS | DESIGNED | CHECKED | DATE |
|---------------------------|-------|-------|---|--|---------|------|
| mm | 2 : 1 | △ | | | | |
| HIROSE ELECTRIC CO., LTD. | | | APPROVED : HY. KOBAYASHI 18.02.26 CHECKED : HY. KOBAYASHI 18.02.26 DESIGNED : TH. KAMEYA 18.02.22 DRAWN : MK. INOUE 18.02.13 | DRAWING NO. EDC-110460-31-00 PART NO. JR16WP-7P(31) CODE NO. CL114-2003-0-31 | | |